| UNIT COOLING TOWER | | | EVADOO TNO EVEDOO | | | [‡] T4144836-DRA-ST | REV. |
|---|--|--|---|-------------------------|---|--|------------------|
| IODEL # | AT 214-3K48 | SCALE NTS | EVA | PCO, INC. | SERIAL | # | DATE 3/3/2025 |
| 2. HEAV 3. MPT [FPT C BFW GVD I FLG C PE DE 4. +UNIT ACCE 5. MAKE 20 psi 6. 3/4" [1 REFE DRAW 7. DIMEI | AN MOTOR LOCATION PIEST SECTION IS UPPER SIDENOTES MALE PIPE THE DENOTES FEMALE PIPE THE DENOTES BEVELED FOR VEMALE DENOTES GROOVED DENOTES FLANGE ENOTES PLAIN END PUBLISHED FOR VEMALE ESSORIES (SEE ACCESSO) E-UP WATER PRESSURE FINITE MIN [137 KPa], 50 psi MAX FINITE MAN TO RECOMMENDED STE | EAD HREAD WELDING .UDE RY DRAWINGS) [344 kPa] LES. EEL SUPPORT | FACE B PLAN VIEW | ACCESS DOOR | FACE C | ACCESS DOOR | FACE D |
| | | | | | FACE A | | |
| T=== | | 7" [17 | [8] 1'-5 1/4" [438] | | | | |
| | <u> </u> | 10'-2 1/4" [3105] | 3'-5 1/2" 5626] | 11'-10 1/2" [3620] | | (M) (2) 14" [350] BFW/GVD INLET | |
| | | 8'-3 1/4" [2521] | 12'-3 3/4" [3753] | | | | |
| • | 13'-11 1/4" - [4248] | 3/8" | 2'-2" [660] 1'-5 3/8" [441] 9" [229] 4 1/8" | 11'-10 1/2" | (2) 4" [100] FPT OVERFLOW (2) 4" [100] FPT DRAIN (2) 1/2" [64] 47'-8 1/2" [14542] | | _ |
| | FACE B | | | | FACE A | | |
| | | | | | | | DRAWN BY: MER |