



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow Rate (GPM), and Temperature (°F) for various configurations. The table lists performance metrics for different coil sizes and flow rates, including GPM, PSI, and inlet/outlet temperatures.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, GPM, PSI, and Flow (First, Second, Third) for various configurations. Includes a sub-header '3/2/2018' and a grid of data points for different coil sizes and flow rates.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns for flow rates (67 to 115) and 32 rows for model numbers (eco-ATWB-H-8-1H18-C12 to eco-ATWB-H-8-3I21-C44). Each cell contains numerical performance data.





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 67-115 for each of the 100 models. Each cell contains numerical performance data.





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 77, 78, 79, 80, 82, 87, 85, 82, 85, 87, 92, 90, 90, 92, 95, 92, 95, 97, 102, 100, 97, 100, 102, 105, 105, 107, 112, 110, 107, 110, 112, 117, 115, 89.6, 102, 98.6, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include models like eco-ATWB-H 9-2H9-U12, eco-ATWB-H 9-2H9-U22, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67, 70, 72, 75, 77, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 115, 89.6, 102, 98.6, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow) and multiple rows of data for various model numbers (e.g., eco-ATWB-H 9-1112-U112, eco-ATWB-H 9-1112-U22, etc.).





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-92, 95-115, 89.6-98.6, First-Third Flow, First-Third Flow) and 100 rows of data representing thermal performance metrics for various coil configurations.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 67-115 for each of the 115 flow rates. The table contains a dense grid of numerical data representing thermal performance metrics.



Evapco eco-ATW-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow, and Temperature (70-115). Rows list various eco-ATW-E models and their corresponding performance metrics.



Evapco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 89.6 to 115. First Flow, Second Flow, Third Flow, First Inlet, Second Inlet, Third Inlet. Rows list various model numbers and their corresponding performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow, and Temperature (70 to 115). Rows list various eco-ATWB-E models and their corresponding performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 75, 77, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 115, 89.6, 102, 98.6, 98.6, 89.6, and 100. Rows include various model numbers like eco-ATWB-H 16-4K14-C12, eco-ATWB-H 16-4K14-C22, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 89.6 to 115. First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include various model numbers like eco-ATWB-H-17-3L12-U12, eco-ATWB-H-17-3L12-U22, etc.



Evapco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and various flow rate and temperature parameters (67, 70, 72, 75, 77, 80, 82, 87, 85, 82, 85, 87, 90, 92, 95, 92, 95, 97, 100, 102, 105, 107, 110, 112, 115, 89.6, 102, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow). The table contains a dense grid of numerical data representing thermal performance metrics.







Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and various flow rate and temperature parameters (67, 70, 72, 75, 77, 80, 82, 87, 85, 82, 85, 87, 92, 90, 87, 90, 92, 95, 92, 85, 82, 92, 95, 97, 102, 100, 97, 100, 102, 105, 102, 105, 107, 112, 110, 107, 110, 112, 117, 115, 89.6, 102, 98.6, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow).





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 75, 77, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 115, 89.6, 90, 98.6, 98.6, First Flow, First PSI, Second Flow, Second PSI, Third Flow, Third PSI. Rows include models like eco-ATWB-H 10-1124-U12, eco-ATWB-H 10-1124-U22, etc.



Evapco Eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 67-115. Rows list various model numbers and their corresponding performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-115, 89.6-102, 98.6-102, First-Third Flow, First-Third Flow) and 100 rows of data representing thermal performance metrics for various models and conditions.



Evapco-ETWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and various flow rate and temperature parameters (67, 70, 72, 75, 77, 80, 82, 87, 85, 82, 85, 87, 92, 90, 87, 90, 92, 95, 92, 95, 97, 102, 100, 97, 100, 102, 105, 107, 112, 110, 107, 110, 112, 117, 115, 89.6, 102, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow). The table contains a large grid of numerical data points for each model and parameter combination.









Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, GPM, PSI, and Flow for various configurations (e.g., eco-ATWB-H 20-3K18-U12, eco-ATWB-H 20-3K18-U22, etc.). The table contains performance data for 100 different models across various flow and pressure conditions.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (70-92) and 100 rows (Model to eco-ATWB-12-4N12-C44). Each row contains numerical data representing thermal performance metrics for various models and conditions.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 75, 77, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 115, 89.6, 98.6, 98.6, 98.6, First Flow, First Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include models like eco-ATWB-12-14N1-U12, eco-ATWB-12-14N1-U22, etc.





Evapco eco-ATWB-E Line Thermal Performance in UGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 89.6 to 93.6. Rows represent different model configurations and their corresponding performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow, and Temperature (89.6 to 50). Rows list various model numbers and their corresponding performance metrics.







Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-115, 89.6-98.6, First-Third Flow, First-Third Flow) and 100 rows of data representing thermal performance metrics for various models and conditions.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-115, 89.6-115, 89.6-115, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow) and 100 rows of data representing thermal performance metrics for various models.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 67-115 (Flow) and 89.6-115 (Flow) for various configurations. The table contains performance data for different models and flow rates.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for flow rate (50-115 GPM), inlet/outlet temperatures (70-115°F), and various performance metrics (Flow, First, Second, Third, etc.).





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-115, 89.6-98.6, First-Third Flow, First-Third Flow) and 100 rows of data. Each row represents a different model configuration and its corresponding performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, GPM, and Flow (89.6 to 115) and rows for various model numbers (e.g., eco-ATWB-24-4K14-U12, eco-ATWB-24-4K14-U22, etc.).



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-115, 89.6-102, 98.6-102, First-Third Flow, First-Third Flow) and 100 rows of data representing thermal performance metrics for various Evapco models.





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow (GPM), and Temperature (°F) for various configurations. The table contains performance data for 100 different models, each with 10 flow rates and 10 temperature points.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and 67-115 (Flow) and 89.6-115 (GPM) for various flow rates. The table contains performance data for different models and flow rates.





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow (70-115), and First Flow (89.6-115). Rows list various model numbers and their corresponding performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 67-115, 89.6-115, 98.6-115, 98.6-115, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include models like eco-ATWB-H 8-3128-C44-Z, eco-ATWB-H 8-3K28-C12-Z, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow (GPM), and Temperature (°F) for various configurations. The table lists performance metrics for different coil sizes and flow rates, including flow velocity and pressure drop.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-102) and 100 rows of data. Each row represents a specific model (e.g., eco-ATWB-H-9-4K9-C44-2) and contains 32 numerical values representing performance metrics. The table is organized into a grid with a header row for the model and a header row for the 32 data points.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-102) and 100 rows of data. Each row represents a specific model (e.g., eco-ATWB-H-9-2114-C44-2) and lists various performance metrics such as flow rate, pressure drop, and efficiency. The table is organized into sections based on coil length (e.g., 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110, 115, 120, 125, 130, 135, 140, 145, 150, 155, 160, 165, 170, 175, 180, 185, 190, 195, 200, 205, 210, 215, 220, 225, 230, 235, 240, 245, 250, 255, 260, 265, 270, 275, 280, 285, 290, 295, 300, 305, 310, 315, 320, 325, 330, 335, 340, 345, 350, 355, 360, 365, 370, 375, 380, 385, 390, 395, 400, 405, 410, 415, 420, 425, 430, 435, 440, 445, 450, 455, 460, 465, 470, 475, 480, 485, 490, 495, 500, 505, 510, 515, 520, 525, 530, 535, 540, 545, 550, 555, 560, 565, 570, 575, 580, 585, 590, 595, 600, 605, 610, 615, 620, 625, 630, 635, 640, 645, 650, 655, 660, 665, 670, 675, 680, 685, 690, 695, 700, 705, 710, 715, 720, 725, 730, 735, 740, 745, 750, 755, 760, 765, 770, 775, 780, 785, 790, 795, 800, 805, 810, 815, 820, 825, 830, 835, 840, 845, 850, 855, 860, 865, 870, 875, 880, 885, 890, 895, 900, 905, 910, 915, 920, 925, 930, 935, 940, 945, 950, 955, 960, 965, 970, 975, 980, 985, 990, 995, 1000).







Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow Rate (70-115 GPM), and Temperature (89.6-111.2°F). Rows list various model numbers and their corresponding performance metrics.



Evapco ECO-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow, and Temperature (70 to 115) and rows for various eco-ATWB-H and eco-ATWB-E models. Each cell contains numerical performance data.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 15 columns for flow rates (50 to 115 GPM) and 15 columns for temperatures (70 to 115 °F). Each cell contains a numerical value representing thermal performance. Includes a 'Model' column on the left and a 'First Flow' column on the far right.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, GPM, PSI, Inlet, and Flow for various temperatures (67 to 115) and flow rates (50 to 340). The table contains performance data for different coil models and configurations.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, GPM, PSI, Inlet, and Flow for various configurations (e.g., eco-ATWB-H 8-419-C44-Z, eco-ATWB-H 8-419-C12-Z, etc.).





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (70-921) and 1000 rows (Model to eco-ATWB-H-8-4L28-C34-2). Each row contains numerical data representing thermal performance metrics for various models and conditions.







Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67, 70, 72, 75, 77, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 115, 89.6, 90, 98.6, 98.6, First Flow, First PSI, First Inlet, Second Flow, Second PSI, Second Inlet, Third Flow, Third PSI, Third Inlet) and multiple rows of data for various model numbers.





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 77, 75, 72, 75, 67, 82, 80, 77, 80, 82, 87, 85, 82, 85, 87, 92, 90, 87, 90, 92, 97, 95, 92, 95, 97, 102, 100, 97, 100, 102, 102, 105, 107, 112, 110, 107, 110, 112, 115, 115, 89.6, 102, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. The table contains a dense grid of numerical values representing thermal performance metrics for various models.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns for flow rates (50-115 GPM) and 32 columns for temperatures (67-115 °F). Rows include model numbers (e.g., eco-ATWB-16-3L14-C44-2) and corresponding performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow Rate (GPM), and Temperature (°F) for various configurations. The table lists performance metrics for different coil models and flow rates, including flow rate, pressure drop, and temperature change.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and various flow rates (57 to 115) and temperatures (60 to 110). The table contains performance data for various Evapco models.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow Rate (GPM), and Temperature (°F) for various configurations. Includes a sub-header '3/2/2018' and a grid of data points for different flow rates and temperatures.





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 75, 77, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 115, 89.6, 90, 98.6, 98.6, First Flow, First PSI, First Inlet, Second Flow, Second PSI, Second Inlet, Third Flow, Third PSI, Third Inlet. Rows include models like eco-ATWB-H 10-2M24-C44-2, eco-ATWB-H 10-2M24-U12-2, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 75, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 117, 115, 89.6, 102, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include models like eco-ATWB-H 10-2K36-C44-Z, eco-ATWB-H 10-2K36-U12-Z, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 77, 75, 62, 65, 67, 77, 82, 80, 77, 80, 82, 87, 85, 82, 85, 87, 92, 90, 87, 90, 92, 95, 92, 95, 97, 102, 100, 97, 100, 102, 102, 105, 102, 105, 107, 112, 110, 107, 110, 112, 117, 115, 89.6, 102, 98.6, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow.



Evapco ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-102) and 100 rows of performance data. Each row represents a specific model and its corresponding flow rate, pressure drop, and other thermal performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 75, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 105, 107, 110, 112, 117, 115, 89.6, 102, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include various model numbers like eco-ATWB-H 20-3K18-C44-Z, eco-ATWB-H 20-3K18-U12-Z, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (70-92) and 100 rows of performance data. Includes headers for Model, Flow, and various temperature points. The table contains a dense grid of numerical values representing thermal performance metrics.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and various flow rates (57-110) and temperatures (70-110). The table contains performance data for various Evapco models, including flow rates in USGPM and temperatures in degrees Fahrenheit.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 77, 75, 72, 75, 77, 82, 80, 77, 80, 82, 87, 85, 87, 92, 90, 87, 90, 92, 97, 95, 92, 95, 97, 102, 100, 97, 100, 102, 107, 105, 102, 105, 107, 112, 110, 107, 110, 102, 105, 100, 89.6, 102, 98.6, 98.6, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include models like eco-ATWB-H 12-3K18-C44-Z, eco-ATWB-H 12-3K18-U12-Z, etc.





Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 77, 75, 72, 75, 77, 82, 80, 77, 80, 82, 87, 85, 82, 85, 87, 92, 90, 87, 90, 92, 97, 95, 92, 95, 97, 102, 100, 97, 100, 102, 102, 105, 107, 112, 110, 107, 110, 112, 115, 115, 89.6, 102, 98.6, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include Model and various GPM/PSI/Inlet values.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67-115, 89.6-98.6, First-Third Flow, First-Third Flow) and 100 rows of data for various model numbers and flow rates.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 3/2/2018, and various flow rate and temperature parameters (67, 70, 72, 75, 77, 80, 82, 85, 87, 90, 92, 95, 97, 100, 102, 107, 105, 102, 105, 107, 110, 107, 110, 112, 117, 115, 89.6, 102, 98.6, 98.6, First Flow, First PSI, Second Flow, Second PSI, Third Flow, Third PSI, Third Flow, Third PSI). Rows include models like eco-ATWB-H 12-3M28-C44-2, eco-ATWB-H 12-3M28-U12-2, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns: 3/2/2018, Model, 67-90, 82-90, 91-90, 97-90, 102-90, 105-90, 107-90, 110-90, 112-90, 117-90, 119-90, 89.6, 102, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include various model codes such as eco-ATWB-H 12-3N36-C44-Z, eco-ATWB-H 12-3N36-U12-Z, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, Flow, and Temperature. The table lists performance data for various Evapco models under different flow and temperature conditions. The first column is '3/2/2018' and the second is 'Model'. The next 30 columns represent flow rates from 50 to 150 GPM. The next 30 columns represent temperatures from 67 to 115 degrees Fahrenheit. The final 30 columns represent flow rates from 89.6 to 115 GPM. The last three columns are labeled 'First Flow', 'Second Flow', and 'Third Flow'.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (3/2/2018, 67, 70, 72, 75, 77, 80, 82, 87, 85, 82, 85, 87, 90, 90, 87, 90, 92, 95, 92, 95, 92, 102, 105, 107, 110, 117, 115, 89.6, 102, 98.6, 98.6, First Flow, First Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow) and multiple rows of data for various model numbers and flow rates.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with 32 columns (70-102) and 100 rows of data. Includes headers for Model, GPM, PSI, Inlet, and Flow. Data points include values for various models like eco-ATWB-H 24-4114-C44-2, etc.



Evapco eco-ATWB-E Line Thermal Performance in USGPM - Galvanized Steel Coil - 30% Ethylene Glycol Water as Process Fluid

Table with columns for Model, 70, 72, 77, 75, 72, 75, 77, 82, 80, 77, 80, 82, 87, 85, 82, 85, 87, 92, 90, 92, 97, 95, 92, 95, 97, 102, 100, 97, 100, 102, 107, 105, 102, 105, 107, 112, 117, 115, 100, 89.6, 102, 98.6, 98.6, 98.6, First Flow, First Flow, First Flow, Second Flow, Second Flow, Second Flow, Third Flow, Third Flow, Third Flow. Rows include models like eco-ATWB-H 24-4M18-C44-Z, eco-ATWB-H 24-4M18-U12-Z, etc.



