UNIT COOLING TOWER		ER .	EVADOO 1		DW	^{rG. #} T3122C48-DRD-ST	REV.
MODEL #	AT 212-4O36	SCALE NTS	EVAPCO, .	INC. evapeo	SER	RIAL #	DATE 3/10/2025
2. HEA 3. MPT FPT BFW GVD FLG 4. +UN ACC 5. MAK 20 p 6. 3/4" REF DRA 7. DIMI	S: FAN MOTOR LOCATION VIEST SECTION IS UPPER: DENOTES MALE PIPE THE DENOTES FEMALE PIPE THE DENOTES BEVELED FOR VENOTES GROOVED DENOTES FLANGE IT WEIGHT DOES NOT INCLESSORIES (SEE ACCESSO) (E-UP WATER PRESSURE SI MIN [137 kPa], 50 psi MAX [19MM] DIA. MOUNTING HO ER TO RECOMMENDED STI WING ENSIONS LISTED AS FOLLO ENGLISH FT-IN METRIC] [mm]	EEAD HREAD WELDING LUDE RY DRAWINGS) [344 kPa] LES. EEL SUPPORT	FACE B PLAN VIEW	ACCESS DOOR	CE A	ACCESS DOOR	FACE D
		2" 10'-4" [3150] 17	"-6 1/4" 5340]	9'-0" (M)		(2) 10" [250] BFW/GVD INLET	
		7'-2 1/4" [2191]	2'-1 1/4"	9'-0" [2743] 17'-3" [5258] 17'-6 3/4" [5353] 18'-0" [5486]	(2) 3" [10 OVERFL (2) 2" [50 MAKE-UP 2 1/2" [64] 1036]	OUTLET 80] FPT	-
	FACE B				<u>CE A</u>		
SHIPPING			OPERATING WEIGHT 44120 lbs+ [20015] kg+	HEAVIEST SECTION 8760 lbs+ [3975]] kg+	NO. OF SHIPPING SECTIONS 4	DRAWN BY: KDS